

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X2 REG TRADESMAN 8' BOX												
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	4050	5953	3398	2555	5500	6000	21500	15080	
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	4050	5953	3398	2555	5500	6000	24000	17580	
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	3260	6741	4129	2612	5500	6000	27000	19780	
RAM 2500 4X2 REG TRADESMAN W/O BOX												
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	4520	5477	3447	2031	5500	6390	21500	14900	
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	4520	5477	3447	2031	5500	6390	24000	17400	
RAM 2500 4X2 REG TRADESMAN 8' BOX CANADA ONLY												
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3950	5953	3398	2555	5500	6000	21500	15080	
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3950	5953	3398	2555	5500	6000	24000	17580	
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	3160	6741	4129	2612	5500	6000	27000	19780	
RAM 2500 4X2 REG TRADESMAN W/O BOX CANADA ONLY												
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	4420	5477	3447	2031	5500	6390	21500	14900	
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	4420	5477	3447	2031	5500	6390	24000	17400	

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X2 CREW TRADESMAN 6.4' BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3650	6345	3558	2787	5500	6000	21500	14680
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3650	6345	3558	2787	5500	6000	24000	17180
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2820	7176	4276	2900	5500	6000	27000	19350
RAM 2500 4X2 CREW TRADESMAN W RAMBOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3530	6473	3554	2919	5500	6000	21500	14560
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3530	6473	3554	2919	5500	6000	24000	17060
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2700	7304	4256	3048	5500	6000	27000	18700
RAM 2500 4X2 CREW TRADESMAN W/O BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	4040	5964	3653	2311	5500	6390	21500	14500
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	4040	5964	3653	2311	5500	6390	24000	17000
RAM 2500 4X2 CREW TRADESMAN 6.4' BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3550	6345	3558	2787	5500	6000	21500	14680
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3550	6345	3558	2787	5500	6000	24000	17180
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2740	7159	4258	2901	5500	6000	27000	19370
RAM 2500 4X2 CREW TRADESMAN RAMBOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3430	6473	3554	2919	5500	6000	21500	14560
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3430	6473	3554	2919	5500	6000	24000	17060
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2600	7304	4256	3048	5500	6000	27000	18700
RAM 2500 4X2 CREW TRADESMAN W/O BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3940	5964	3653	2311	5500	6390	21500	14500
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3940	5964	3653	2311	5500	6390	24000	17000

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X2 CREW TRADESMAN 8' BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3550	6453	3678	2774	5500	6000	21500	14580
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3550	6453	3678	2774	5500	6000	24000	17080
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2680	7324	4473	2850	5500	6000	27000	19200
RAM 2500 4X2 CREW TRADESMAN W/O BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	4030	5966	3712	2254	5500	6390	21500	14420
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	4030	5966	3712	2254	5500	6390	24000	16920
RAM 2500 4X2 CREW TRADESMAN 8' BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3450	6453	3678	2774	5500	6000	21500	14580
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3450	6453	3678	2774	5500	6000	24000	17080
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2580	7322	4469	2853	5500	6000	27000	19200
RAM 2500 4X2 CREW TRADESMAN W/O BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3930	5966	3712	2254	5500	6390	21500	14420
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3930	5966	3712	2254	5500	6390	24000	16920

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X4 MEGA BIG HORN/LONE STAR 6.4' BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	3.73	10000	2970	7035	4041	2994	5500	6390	21500	14000
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	4.10	10000	2970	7035	4041	2994	5500	6390	24000	16500
6.7L 16 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2130	7873	4822	3052	6000	6040	25265	16520
RAM 2500 4X4 MEGA BIG HORN/LONE STAR RAMBOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	3.73	10000	2820	7180	4039	3141	5500	6390	21500	13850
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	4.10	10000	2820	7180	4039	3141	5500	6390	24000	16350
6.7L 16 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	1980	8018	4820	3199	6000	6040	25265	15070
RAM 2500 4X4 MEGA BIG HORN/ 6.4' BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	3.73	9900	2870	7035	4041	2994	5500	6390	21500	14000
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	4.10	9900	2870	7035	4041	2994	5500	6390	24000	16490
6.7L 16 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2030	7873	4822	3052	6000	6040	25265	15520
RAM 2500 4X4 MEGA BIG HORN RAMBOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	3.73	9900	2720	7180	4039	3141	5500	6390	21500	13850
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FF75-LCV TRANSMISSION	4.10	9900	2720	7180	4039	3141	5500	6390	24000	16350
6.7L 16 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	1880	8018	4820	3199	6000	6040	25265	14070

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X4 REG TRADESMAN 8' BOX

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	3.73	10000	3680	6317	3696	2620	5500	6000	21500	14710
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	4.10	10000	3680	6317	3696	2620	5500	6000	24000	17210
6.7L I6 CUMMINS TURBO DIESEL ENGINE	8-SPD AUTOMATIC 88RFE TRANSMISSION	3.73	10000	2830	7173	4494	2678	5750	6000	27000	19350

RAM 2500 4X4 REG TRADESMAN W/O BOX

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	3.73	10000	4170	5829	3747	2082	5500	6390	21500	14550
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	4.10	10000	4170	5829	3747	2082	5500	6390	24000	17050

RAM 2500 4X4 REG TRADESMAN 8' BOX CANADA ONLY

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	3.73	9900	3570	6329	3704	2625	5500	6000	21500	14700
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	4.10	9900	3570	6329	3704	2625	5500	6000	24000	17200
6.7L I6 CUMMINS TURBO DIESEL ENGINE	8-SPD AUTOMATIC 88RFE TRANSMISSION	3.73	9900	2720	7179	4498	2681	5750	6000	27000	19350

RAM 2500 4X4 REG TRADESMAN W/O BOX CANADA ONLY

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	3.73	9900	4070	5826	3673	2153	5500	6390	21500	14550
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8FP75-LCV TRANSMISSION	4.10	9900	4070	5826	3673	2153	5500	6390	24000	17050

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X4 CREW TRADESMAN 6.4' BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3380	6623	3828	2795	5500	6000	21500	14410
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3380	6623	3828	2795	5500	6000	24000	16910
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2520	7485	4628	2857	5750	6000	27000	19040
RAM 2500 4X4 CREW TRADESMAN RAMBOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3230	6767	3831	2936	5500	6000	21500	14260
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3230	6767	3831	2936	5500	6000	24000	16760
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2360	7638	4632	3006	5750	6000	27000	18870
RAM 2500 4X4 CREW TRADESMAN W/O BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3730	6269	3948	2321	5500	6390	21500	14190
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3730	6269	3948	2321	5500	6390	24000	16690
RAM 2500 4X4 CREW TRADESMAN W/ PWR -WAGON EQUIPMENT 6.4' BOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	8565	1660	6907	4080	2827	4750	6200	18000	10620
RAM 2500 4X4 CREW TRADESMAN W/ PWR -WAGON EQUIPMENT RAMBOX											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	8565	1510	7052	4078	2974	4750	6200	18000	10380
RAM 2500 4X4 CREW TRADESMAN 6.4' BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3280	6622	3833	2790	5500	6000	21500	14410
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3280	6622	3833	2790	5500	6000	24000	16910
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2380	7516	4647	2869	5750	6000	27000	19010
RAM 2500 4X4 CREW TRADESMAN RAMBOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3130	6767	3831	2936	5500	6000	21500	14260
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3130	6767	3831	2936	5500	6000	24000	16760
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2250	7653	4647	3006	5750	6000	27000	17720
RAM 2500 4X4 CREW TRADESMAN W/O BOX CANADA ONLY											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3630	6269	3948	2321	5500	6390	21500	14190
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3630	6269	3948	2321	5500	6390	24000	16690

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. Maximum Capability.

2019 RAM 2500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 2500 4X4 CREW TRADESMAN 8' BOX

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3190	6805	3989	2816	5500	6000	21500	14220
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3190	6805	3989	2816	5500	6000	24000	16720
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	10000	2340	7660	4766	2895	5750	6000	25525	17390

RAM 2500 4X4 CREW TRADESMAN W/O BOX

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	10000	3640	6356	4012	2344	5500	6390	21500	14030
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	10000	3640	6356	4012	2344	5500	6390	24000	16530

RAM 2500 4X4 CREW TRADESMAN 8' BOX CANADA ONLY

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3090	6811	3993	2819	5500	6000	21500	14220
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3090	6811	3993	2819	5500	6000	24000	16720
6.7L I6 CUMMINS TURBO DIESEL ENGINE	6-SPD AUTOMATIC 68RFE TRANSMISSION	3.73	9900	2230	7666	4769	2897	5750	6000	25525	17380

RAM 2500 4X4 CREW TRADESMAN W/O BOX CANADA ONLY

Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	3.73	9900	3530	6373	3981	2392	5500	6390	21500	14020
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	4.10	9900	3530	6373	3981	2392	5500	6390	24000	16510

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. Maximum Capability.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 REG CAB TRADESMAN W/8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7680	6319	3396	2923	5500	9750	21500	14710
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7680	6319	3396	2923	5500	9750	25000	18210
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4660	6037	3402	2635	5500	7000	21500	14990
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4660	6037	3402	2635	5500	7000	24000	17490
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4700	6803	4155	2648	5500	7000	28300	21030
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6910	7094	4148	2946	5500	9750	28300	20740
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6910	7094	4148	2946	5500	9750	30300	22740
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	4520	6982	4275	2707	5500	7000	34630	26990
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	6570	7430	4324	3106	5500	9750	41600	33700
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	6570	7430	4324	3106	5500	9750	43000	35100

RAM 3500 4X2 REG CAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	5190	5506	3441	2065	5500	7000	21500	14870
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	5190	5506	3441	2065	5500	7000	24000	17370

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 CREW CAB TRADESMAN W/6.5' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4300	6400	3585	2815	5500	7000	21500	14630
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4300	6400	3585	2815	5500	7000	24000	17130
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION-6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4260	7241	4341	2900	5500	7000	28300	20590
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	4120	7383	4450	2932	5500	7000	32240	24320

RAM 3500 4X2 CREW CAB TRADESMAN W/RAMBOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4160	6545	3583	2962	5500	7000	21500	14490
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4160	6545	3583	2962	5500	7000	24000	16990
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION-6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4110	7386	4363	3023	5500	7000	28300	20440
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	3970	7528	4473	3055	5500	7000	32240	23350

RAM 3500 4X2 CREWCAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4720	5984	3670	2314	5500	7000	21500	14480
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4720	5984	3670	2314	5500	7000	24000	16980

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 CREW CAB TRADESMAN W/8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11100	4530	6567	3727	2840	5500	7000	21500	14460
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11100	4530	6567	3727	2840	5500	7000	24000	16960
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7050	6954	3754	3201	5500	9750	21500	14080
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7050	6954	3754	3201	5500	9750	25000	17580
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12000	4620	7385	4483	2902	5500	7000	28300	20450
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6170	7833	4542	3291	5500	9750	28300	20000
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6170	7833	4542	3291	5500	9750	30300	22000
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12000	4470	7527	4597	2931	5500	7000	33670	25650
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5950	8050	4663	3386	5500	9750	41600	33080
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5950	8050	4663	3386	5500	9750	43000	34480

RAM 3500 4X2 CREWCAB TRADESMAN W/OBOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11100	5080	6019	3749	2270	5500	7000	21500	14370
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11100	5080	6019	3749	2270	5500	7000	24000	16870

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.												
RAM 3500 4X4 MEGA CAB BIG HORN/LONE STAR 6.5' BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	6630	7374	4033	3341	5500	9750	21500	13660
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	6630	7374	4033	3341	5500	9750	25000	17160
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4420	6978	4011	2967	5500	7000	21500	14050
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4420	6978	4011	2967	5500	7000	24000	16550
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4330	7968	4805	3163	6000	7000	28300	19860
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	5670	8332	4851	3481	6000	9750	28300	19500
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	5670	8332	4851	3481	6000	9750	30300	21500
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4220	8079	4916	3162	6000	7000	32710	24060
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5420	8577	4990	3588	6000	9750	41600	32550
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5420	8577	4990	3588	6000	9750	43000	33020
RAM 3500 4X4 MEGA CAB BIG HORN/LONE STAR RAMBOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4280	7123	4009	3114	5500	7000	21500	13910
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4280	7123	4009	3114	5500	7000	24000	16410
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4190	8114	4834	3280	6000	7000	28300	19720
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4080	8224	4945	3279	6000	7000	32710	23280

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X4 REG CAB TRADESMAN 8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4600	6403	3698	2704	5500	7000	21500	14630
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4600	6403	3698	2704	5500	7000	24000	17130
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7280	6715	3710	3005	5500	9750	21500	14310
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7280	6715	3710	3005	5500	9750	25000	17810
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6390	7614	4496	3118	6000	9750	28300	20220
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6390	7614	4496	3118	6000	9750	30300	22220
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	11800	4610	7195	4442	2753	6000	7000	28300	20640
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	6160	7842	4620	3222	6000	9750	41600	33290
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	6160	7842	4620	3222	6000	9750	43000	34690
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4460	7341	4551	2790	6000	7000	34540	26440

RAM 3500 4X4 REG CAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	5130	5869	3742	2127	5500	7000	21500	14510
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	5130	5869	3742	2127	5500	7000	24000	17010

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.												
RAM 3500 4X4 CREW CAB TRADESMAN 6.5' BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4270	6728	3853	2876	5500	7000	21500	14300
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4270	6728	3853	2876	5500	7000	24000	16800
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC.68RFE	SRW	3.73	11800	4340	7460	4563	2897	6000	7000	28300	20370
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4180	7622	4683	2939	6000	7000	32580	24490
RAM 3500 4X4 CREW CAB TRADESMAN RAMBOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4140	6863	3872	2991	5500	7000	21500	14170
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4140	6863	3872	2991	5500	7000	24000	16670
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC.68RFE	SRW	3.73	11800	4200	7605	4561	3044	6000	7000	28300	20230
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4030	7767	4681	3086	6000	7000	32580	23750
RAM 3500 4X4 CREWCAB TRADESMAN W/O BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4720	6278	3927	2351	5500	7000	21500	14180
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4720	6278	3927	2351	5500	7000	24000	16680

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X4 CREW CAB TRADESMAN 8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	6680	7317	4058	3259	5500	9750	21500	13710
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	6680	7317	4058	3259	5500	9750	25000	17210
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4480	6920	4017	2903	5500	7000	21500	14110
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4480	6920	4017	2903	5500	7000	24000	16610
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4580	7723	4751	2973	6000	7000	28300	20110
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	5840	8159	4818	3341	6000	9750	28300	19670
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	5840	8159	4818	3341	6000	9750	30300	21670
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4420	7878	4872	3005	6000	7000	33610	25150
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5600	8396	4955	3441	6000	9750	41600	32730
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5600	8396	4955	3441	6000	9750	43000	34130

RAM 3500 4X4 CREWCAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	5020	6377	4050	2326	5500	7000	21500	14010
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	5020	6377	4050	2326	5500	7000	24000	16510

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.