

REAR DOOR VAN RAMP



- Easy Installation*
- Mounts to floor of van inside doorway
- Three sections, manually operated with spring assist
- Easily operated by one person
- Stores vertically inside doorway
- Durable welded construction
- Anti-slip, high traction surface
- Accommodates wheelchairs and scooters with various wheel configurations
- Not compatible with vans that have stow away seating

NOTE: Minimum inside door opening required for this ramp is 34". Minimum requirement for floor to ceiling opening 7' ramp - 37", 8' ramp - 41".

LIMITED LIFETIME WARRANTY



Item Number	Length	Unfolded Size	Folded Height	Weight	Capacity**
VAN727*	7'	7' x 27"	36"	72 lbs.	800 lbs.
VAN827	8'	8' x 27"	40"	77 lbs.	800 lbs.

Not sure which ramp length you need? Refer to pages 18 - 19 to help you.

* Conversion kit is required if rear door opening contains a threshold.
 ** Maximum ramp capacity: 400 lbs. (one axle) - 800 lbs. (two axles).

LIMITED LIFETIME WARRANTY

SLOPE REDUCER



- Reduces ramp slope and eases entry
- Lightweight, durable aluminum
- Anti-slip high traction surface
- Lightweight, easy-to-handle and set up
- For use with van ramp models VAN727 and VAN827

Slope too steep? Here's the solution!

Item Number	Description	Size	Weight	Capacity*
VAN2426.75	One Piece	24" x 26 $\frac{3}{4}$ "	8 lbs.	600 lbs.